

Zerust® Axxanol™ Spray-G

CORROSION INHIBITING SPRAYABLE GREASE

PRODUCT INFORMATION

FEATURES

- Sprayable
- Long-term protection
- Multimetal protection
- Resistant to water
- Easy to remove
- Safe for paint and plastic

BENEFITS

- Reduces corrosion
- Reduces need for rework
- Saves money & resources
- Comes with Zerust® global on-site support
- Can be used on its own or in packaging to extend protection

For superior corrosion protection in a sprayable grease, use Zerust® Axxanol™ Spray-G. The product has an oily grease consistency and provides advanced corrosion protection for parts and equipment even outdoors.

Zerust Corrosion Protection

Axxanol Spray-G is a hydrophobic corrosion inhibiting coating that protects in extreme conditions. This unique product protects like a light grease and goes on like an oil. It provides ferrous and non-ferrous multimetal protection for up to one year outdoors and up to two years indoors. Axxanol Spray-G outperforms many other corrosion preventative coatings and is easier to apply and remove, saving time and costs associated with corrosion.

Light Lubricant

Axxanol Spray-G can be used as a light lubricant while it provides exceptional corrosion protection. The product is resistant to water and is compatible with most rubber and plastic materials. Test on a small area before use.

Protect bare metals in highly aggressive environments with Zerust® Axxanol™ Spray-G sprayable grease and reduce corrosion incidences and costs.

APPLICATION EXAMPLE

ZERUST® AXXANOL™ SPRAY-G IS SPRAYED ON TO A LARGE PIECE OF MACHINERY IN PREPARATION FOR OVERSEAS SHIPPING AND OUTDOOR STORAGE.



APPLICATION TYPE

CORROSION PROTECTION FOR:



ORDERING INFORMATION

■ AVAILABILITY/PART NUMBER

5 Gal Pail (35 lbs): 350-M-00023PL
55 Gal Drum (400 lbs): 350-M-00023DR

■ PROTECTION TYPE

Ferrous and non-ferrous multiple metal type corrosion protection capability.

■ PROTECTION LIFE

When properly spray applied, Spray-G will protect metals for up to 1 year outdoors and up to 2 years under shelter.

■ FLASH POINT

Above 200° F (93° C)

■ COVERAGE

Up to 300 ft² (28m²) per gallon

■ SHELF LIFE & HANDLING

Shelf life of 2 years when stored in original container, at 85° F (29°C) or less and out of direct sunlight.

■ DISPOSAL

Dispose of in accordance with all applicable federal, state and local regulations.

QUESTIONS?

Contact Customer Service:
Call: +1 (763) 225-6600
email: sales@zerust.com



A product of:
Northern Technologies International Corporation
4201 Woodland Road
P.O. Box 69
Circle Pines, MN 55014
PH: +1 (763) 225-6600
FAX: +1 (763) 225-6645
EMAIL: sales@zerust.com
WEB: www.zerust.com

DIRECTIONS FOR USE:

1. Make sure parts and equipment are clean and dry.
2. Wear gloves to avoid corrosion from fingerprints.
3. The surface temperature should be near to the ambient temperature when coating.
4. Stir product well. Product needs to be at room temp or warmer to spray uniformly.
4. Spray-on a thin uniform layer of Axxanol™ Spray-G using a pressurized airless sprayer.

REMOVAL:

Zerust® Axxanol Spray-G can be removed by using any commercially available solvent or water-based alkaline cleaner. Always check to see if removal of Axxanol Spray-G is required prior to the use of the protected item.

ICT®700 SERIES OVERVIEW: LIQUID ADDITIVES & COATINGS

Product Name	Metals Protected	Estimated Protection Life Outdoors	Estimated Protection Life Indoors*	Formulation Base	Surface Finish
Axxatec™ 77C (4% dilution)	Iron, steel, aluminum, brass, zinc and copper	Not recommended	4 months	Water-based	Thin, cloudy, visible
Axxatec™ 80C (2% dilution)	Iron, steel and cast iron	Not recommended	6 months	Water-based	Dry to touch, clear
Axxatec™ 80C (7.5% dilution)	Iron, steel and cast iron	Not recommended	12 months	Water-based	Dry to touch, clear
Axxanol™ 33CD	Iron, steel and copper	Not recommended	6 months	Solvent-based	Very thin oil, dry to touch
Axxanol™ 34CD	Iron, steel, aluminum, zinc, copper and solder	Not recommended	6 months	Solvent-based	Very thin oil
Axxanol™ 33	Iron, steel, aluminum, zinc, copper and solder	Not recommended	8 months	Oil-based	Thin oil
Axxanol™ 46-BIO	Iron, steel, aluminum, zinc and solder	3 months	12 months	Bio-based	Thin oil
Z-Maxx LV	Iron, steel, aluminum, brass, zinc and copper	12 months	24 months	Oil-based	Light grease (NLGI 0)
Z-Maxx	Iron, steel, aluminum, brass, zinc and copper	12 months	24 months	Oil-based	Thick, grease (NLGI 2)
Axxanol™ Spray-G	Iron, steel, aluminum, brass, zinc and copper	12 months	24 months	Oil-based	Oily grease

* Water-based product test results are per ASTM D2247 humidity chamber testing. Oil- and solvent-based product test results are per ASTM B117 salt spray testing. Estimated indoor protection life results are rated for indoors or under shelter. Check with your Zerust® sales representative for details on Zerust® packaging products which extends protection life to five years and beyond.

OTHER PRODUCTS AVAILABLE

ICT®500 Series: Packaging Films

Our most widely used series of products. A variety of films offer short or long-term corrosion protection for parts and equipment during storage or shipment.

ICT®600 Series: Rust Removers

Highly effective rust removers for light to severe rust removal. All ICT®600 series rust removers are non-toxic, non-hazardous & non-corrosive.

Warranty and Disclaimer information:

We guarantee our product conforms to documented quality specifications. Product information subject to change without notice. We make no warranty of any kind expressed or implied. All statements, technical information and recommendations contained herein are based on testing and experiences NTIC believes to be reliable, but the accuracy or completeness thereof is not guaranteed. See www.zerust.com/warranty.

©2011 Northern Technologies International Corporation (NTIC). All Rights Reserved. NTIC is the owner of the following trademarks: NTI®, NIC®, ZERUST®, The ZERUST People®, MATCH TECH®, Cor-Tab®, Plastabs®, ICT®, COR-SCI®, Z-CIS® and the Color "Yellow". EXCOR®, VALENO®, ABRIGO® and UNICO® are registered trademarks of EXCOR GmbH, a Joint Venture Partner of NTIC